



601L POWER AMPLIFIER

1 Watt Linear UHF Amplifier For Signal Distribution

- 500 KHz – 1,000MHz
Frequency Range
- Rugged Compact Design
- Operates into any load
- Low Distortion

High Reliability

Complete stability and instantaneous fail-safe protection ensure operation in to mismatch and overdrive conditions.

The 601L will withstand a + 13dBm Input signal for all load conditions.



The 601L Broadband Amplifier is a rugged source of RF power suitable for a variety of UHF signal distribution and general laboratory applications. It is a compact fully solid state design. It features low-level intermodulation distortion and inherent protection against short and open circuit loads. The 601L amplifies the inputs of AM, FM, SSB, pulse and other complex modulations within its output and bandwidth capability.

Flexible Operation

The 601L produces 1 Watt of Class A linear output power over a frequency range of 500 KHz to 1000 MHz with a nominal gain of 40 dB (± 2.5 dB). In order to provide exceptionally low levels of IMD, highly linear RF devices are used, with feedback, in the driver and output amplifier stages. All harmonics are more than 22 dB below the fundamental frequency at 1.0 Watt Pout.

Rugged Design

An integral power supply allows for operation directly from an input of 115/230 V single phase. Both the power supply and the forced air cooling are conservatively designed for operation over a wide temperature range.



1387 Brighton Henrietta Townline Rd.
Rochester, NY 14623
Tel: (585) 214 0598
Fax: (585) 214 0580
www.eandiltd.com

601L POWER AMPLIFIER

Class of Operation
Class A

Frequency Range
500 KHz to 1000MHz

Rated Output Power
1.0 Watt (0.8 – 1000 MHz)

Gain
40 dB

Gain Flatness
+/- 2.5dB

Input For Rated Output
0.1 mw (-10dBm)

Input Impedance / VSWR
50Ω 2.5:1

Output Impedance / VSWR
50Ω 3.0:1

Harmonic Level
< -22 dBc @ 1.0 W output

Ruggedness
∞:1 VSWR

Noise Figure
10 dB Typical

Spurious Output: <-60dBc

Primary Power:
100 – 240 VAC 47-63 Hz.
1 A @ 120 V
0.5 A @ 240 V

Temperature Range
0 to 45 degrees C

Cooling
Forced Air

Weight
10 lbs. (4.5 Kg)

Front Panel
Controls: AC On/Off
Indicators: AC Power On
Connectors: RF Input/Output (BNC)

Accessories Supplied

Operation Manual
AC line cord

Dimensions
(H x W x D)
3.5" x 7.9" x 15"
89 mm x 201.4 mm x 381.8 mm



1387 Brighton Henrietta Townline Rd.
Rochester, NY 14623
Tel: (585) 214 0598
Fax: (585) 214 0580
www.eandiltd.com